



## CrashCamMini™

The CrashCam™ mini HD POV is a rugged, ultra-compact high-G and vibration-rated camera designed to withstand harsh, space-limited environments like all cameras in the CrashCam™ mini family. With its uniquely-designed image processing and intuitive MotionPad software, the HD POV is the only CrashCam™ model designed to provide 1080p LIVE and INSTANT REPLAY of images. The camera supports 1920 x 1080 resolution with up to 1,300 fps and comes standard with 8GB DDR RAM, USB-C interface and C-mount lens mount. Additional configuration options include a motorized Micro Four Thirds lens mount for non-high-G applications. IDT's optional airborne feature includes special nano coating to protect against condensation due to rapid changes in ambient conditions.

- Ultra-compact form factor
- HDSDI output
- MicroSD compatible

### APPLICATIONS

Automotive, Research

### KEY FEATURES

Maximum Resolution	1920 x 1080
Maximum FPS @ Maximum Res	1,300 fps
Operating Temperature	-40+50°C / -40+122°F

### FRAME PROPERTIES

Sensor Type	CMOS - Proprietary
Sensor Size	19.2 x 10.8 mm
Sensor Format	1.3 inch
Pixel Size (micron)	7.5 x 7.5 µm
Pixel Depth	12 bit mono 36 bit color
Sensitivity	30,000 ISO Mono, 10,000 ISO Color
Min. Exposure Time	1µs (*Shorter Integration optional)
Array	3.7 megapixel
Quantum Efficiency	60%

### MECHANICAL

Weight	0.27 kg or 0.59 lbs
Dimensions	44 x 44 x 70 mm (W x H x L)
Shock & Vibration	Shock: 200G / Vibration: 40G - All axes
Mount	C-Mount (Standard), Motorized MFT

### TRIGGERING AND SYNCHRONIZATION

Sync In	Phase-lock TTL, 1PPS
Sync Out	Frame sync / Strobe
Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
HDSDI	Standard

## Model CCM-POV



### POWER

Input Voltage	7.5-14VDC
---------------	-----------

### COMMUNICATION INTERFACE

Ethernet	2.5 Gbps
----------	----------

### EMBEDDED LOGIC

Debayering	Color Cameras Only
Temporal Noise Reduction	Standard
Dynamic Noise Reduction	Standard
User defined ROI's and LUT's	Standard
Frame to frame Auto-Exposure and Motion Trigger	Standard

### IMAGE CAPACITY

DDR	8GB
MicroSD	Up to 400GB (Tested)

### SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
MotionPad	Apple iOS, Windows
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF