



Phoenix

Model PHX-UHD

The XStream Phoenix Series of cameras is revolutionizing streaming in high speed. The model UHD produces crisp LIVE and INSTANT REPLAY image streams at a resolution of 3480x2160 at 3,280 fps. Cameras come standard with a motorized MFT lens mount and IDT's XStreamLink fiber interface to support distances up to 2 kilometers.

- Compact form factor
- User-Friendly Operation
- Simultaneous LIVE and INSTANT REPLAY
- Fiber Interface for Long Distances

APPLICATIONS

Aerospace, Defense, Military Range Tracking, Sports Biomechanics, R&D

KEY FEATURES

Maximum Resolution	3840 x 2880
Maximum FPS @ Maximum Res	2,450
Operating Temperature	-40+50°C / -40+122°F

FRAME PROPERTIES

Sensor Type	CMOS - Proprietary
Sensor Size	20 x 15 mm
Sensor Format	1.3 inch
Pixel Size (micron)	5.2 x 5.2 μ m
Pixel Depth	12 bit mono 36 bit color
Sensitivity	15,000 ISO Mono 5,000 ISO Color
Min. Exposure Time	1 μ s
Array	11 megapixel
Quantum Efficiency	60%

MECHANICAL

Weight	0.71 kg or 1.5 lbs
Dimensions	48 x 84 x 153 mm (W x H x L)
Mount	Motorized MFT (Standard)



POWER

Input Voltage	12 VDC
---------------	--------

COMMUNICATION INTERFACE

Fiber Optic	XStreamLink
-------------	-------------

EMBEDDED LOGIC

Debayering	Color Cameras Only
Temporal Noise Reduction	Standard
Dynamic Noise Reduction	Standard
User defined ROI's and LUT's	Standard

SOFTWARE

XStream Motion Monitor	Windows 64
Motion Studio	Windows 64
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF