



# SPECIFICATION SHEET

## NX-Air

Model NXA5

The NX-Air Series is an upgraded package of the NX that includes an on-board battery that allows for over one hour of untethered operation. The NX-Air can also be configured with an optional WiFi™ module for wireless operation. In this configuration, the camera is fully autonomous and can be operated remotely using a laptop, tablet or Mac iOS device like an iPad®. Power Supply, High G Universal Mounting Plate and Break-out cable for easy out-of-the-box operation are included.

- Standalone image capture
- Durable, compact, High G rated
- Supports many resolutions and speed grades

### APPLICATIONS

Laboratory, R&D, Media

### KEY FEATURES

Maximum Resolution	2336 x 1728
Maximum FPS @ Maximum Res	730 fps
Maximum FPS @ Maximum Res (Plus Mode)	1,460 fps
Maximum FPS	110,000 fps @ 2336 x 8
Operating Temperature	-40+50 °C / -40+122 °F

### FRAME PROPERTIES

Sensor Type	CMOS - Proprietary
Sensor Size	16.4 x 12.1 mm
Sensor Format	1 inch
Pixel Size (micron)	7.00 x 7.00 um
Pixel Depth	10 bit mono 30 bit color
Sensitivity	3000 ISO Mono 1000 ISO Color
Min. Exposure Time	1µs (*Shorter Integration optional)
Array	4.0 megapixel
Quantum Efficiency	1

### MECHANICAL

Weight	0.78 kg or 1.72 lbs
Dimensions	63 x 76 x 97 mm (W x H x L)
Shock & Vibration	Shock: 200G / Vibration: 40G - All axes
Mount	C-Mount (Standard) , F Adaptor (Optional)

### TRIGGERING AND SYNCHRONIZATION

Sync In	Phase-lock TTL, 1PPS
Sync Out	Frame sync / Strobe
Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
IRIG	Optional (In place of GPS)
GPS Time Code	Standard



### POWER

Input Voltage	24 VDC
Battery	Operation and battery back-up up to 2 hours

### COMMUNICATION INTERFACE

Ethernet	100/1000BaseT
WiFi	Optional

### EMBEDDED LOGIC

Debayering	Color Cameras Only
Temporal Noise Reduction	Standard
User defined ROI's and LUT's	Standard
Frame to frame Auto-Exposure and Motion Trigger	Standard

### IMAGE CAPACITY

DDR	5GB
-----	-----

### SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF